

Component Side (CS)	top(1) pads(17) vias(18)
Contours and additional routings	dimension(20)
Silkscreen CS	tplace(21) tnames(25)
Soldermask SS	tstop(29)
Drills plated,	drills(44)
Drills nonplated	holes(45)

Layers:		
Nr		Name
1	Red	Top
2	Dark Blue	Route2
3	Dark Red	Route3
16	Blue	Bottom
17	Green	Pads
18	Light Green	Vias
19	Olive	Unrouted
20	Light Grey	Dimension
21	Grey	tPlace
22	Grey	bPlace
23	Grey	tOrigins
24	Grey	bOrigins
25	Grey	tNames
26	Grey	bNames
27	Grey	tValues
28	Grey	bValues
29	Diagonal Lines	tStop
30	Diagonal Lines	bStop
31	Diagonal Lines	tCream
32	Diagonal Lines	bCream
33	Diagonal Lines	tFinish
34	Diagonal Lines	bFinish
35	Diagonal Lines	tGlue
36	Diagonal Lines	bGlue
37	Grey	tTest
38	Grey	bTest
39	Dark Red	tKeepout
40	Dark Blue	bKeepout
41	Dark Red	tRestrict
42	Dark Blue	bRestrict
43	Green	wRestrict
44	Grey	Drills
45	Grey	Holes
46	Teal	Milling

Innerlayer 1	Route2(2)
Innerlayer 2	Route3 (3)
Solder Side (SS)	bottom(16) pads(17) vias(18)
Silkscreen SS	bplace(22) bnames(26)
Soldermask CS	bstop(30)

The setting for covering vias can be found **under „edit – design rules“** and can be adjusted under „mask – limit“
 For a correct size of the Text, the option “User Interface”, “Always Vector Font” and “Persistant in this drawing” must be true.

Please note: If additional or different Layers are used, please specify this on your order.